

Hydroxyl Generators Optimum Model by Environment





















	Odorox® Model	SanX™	Slimline™	IDU™	Oasis™	MDUTM	Boss TM	Boss XL3™	DeconScrubber™	¹ MVP 14™	MVP 48™
		Odour/Decon	Odour/Decon	Decon	Odour/Decon	Decon	Odour	Odour	Odour/Particulate	Odour/Decon	Odour/Decon
	Number of Optics	1	1	2	1	2	2	3	3	14	48
	CFM Rating	150-500	150-500	250-630	250-630	250-630	250-630	air mover	1,500/HEPA	1,400	5,000
Square											
Footage	Moderate Contamination		600	1,250	1,000	1,250	2,000	2,500	2,500	solution b	ased on
	Heavy Contamination	300	300	700	500	700	1,000	1,500	2,000	evaluation ar	nd test data
Disaster Resto						X	X	X	X	X	X
Contents Clea							X	X	X	X	X
	tors Office, Clinics	X	X	X		X			X		
Senior Care 8		X	Χ	X	X	X					
	mercial Buildings	X	X	X	X	X			X		
Funeral Home		X	X			Χ			X		
	ar, Games Room			X	X		X		X		
	Gym, Locker Room	X	X	X		X			X		
	Pet Store, Shelters	X	X	X		X			X		
Contractor & [X	Χ			X	X	X		
	uilding Maintenance	X	X			X	X	X	X		
Boats & RV's		X	X	X	X	Χ	X				
	ealership & Rentals						X				
	aces of Worship	X	X	X		X			X		
	olice & Firehouse	X	X	X		X	X		X	X	
	ab, Dry Cleaner		.				X	X	X		
Food Process		X	X			X			X	X	
Trash/Dumpst			\		\		X	X		X	
Nail & Hair Sa		X	X	X	X		X				
Heavy Industr	ial							Χ	X	X	X
Livestock							\ <u>'</u>			X	X
Greenhouse		\	\ /		\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \		X	X	X	X	
House, Townh	nome, Apartment	X	X	X	X	X	X				